

# **SPRIT 雅各科技股份有限公司**

SPRIT INNOTECH INC.

No.10, Luke 1st Rd., Kaohsiung Science Park-

Lujhu Dist., Kaohsiung City, Taiwan (R.O.C.)

高雄市路竹區路科一路 10 號 TEL : 886-7-6955588 FAX : 886-7-6955599

Website:www.spirittw.com

## **SPRIT-510A HEAT ACTIVATED TAPE – RADIAL ADHESIVE TAPE**

### **Applications**

- Apply to radial taping of electronic components sequencing

### **Features**

- Heat activated acrylic solvent based adhesive
- Superior holding power
- The adhesive activated when temperature rises to 110~180°C, elapses when temperature drops back to room temperature

### **Physical**

|  |                         |
|--|-------------------------|
| <b>Property:</b> Backing               | Crepe Paper             |
| Adhesive System                        | Heat Activated Adhesive |
| Total Thickness (mm)                   | 0.18 ± 0.02             |
| Tensile Strength (kg / 25mm)           | 4.5                     |
| Elongation (%)                         | 10 ± 5                  |
| Adhesion to Stainless Steel (g / 25mm) | 600                     |
| Temperature Resistance (°C)            | 110~180                 |
| Holding Power (hr)                     | 10                      |

### **Size**

|                   |                       |
|-------------------|-----------------------|
| Paper Width (mm): | 6mm, 12mm, 13mm, 15mm |
| Length (mtrs):    | 500M, 2000M, 3000M    |

### **For more available sizes please contact our sales representatives**

**Note** While we believe above information to be reliable, the statements and information herein are only for general guidance and are not warrants of guarantees for accuracy and completeness. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Our standard terms and condition of sales apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE ARE EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice in our products and publications. User is responsible for determining whether our product is fit for a particular purpose and suitable for user's application. If you are in any doubt, our technical support staff will be glad to advise you.